Ei171RF



RadioLINK Strobe Light



- · Flashing strobe light for daytime rooms
- Mains powered with rechargeable lead acid back-up
- · Wireless interconnecton with SmartLINK, RadioLINK+ and RadioLINK Alarms
- 5 year guarantee



Description

The Eil71RF is a RadioLINK alarm accessory that is designed to give warning to the deaf and hard of hearing if their alarm system has activated. It consists of a mains powered strobe light with a rechargeable battery back up. For daytime rooms

Technical

RF Frequency (MHz)	868.499	RF Range (m)	>100 in free a
RE Frequency (MIDZ)	000.499	RF Range (III)	-100 II

Blue - RF transmission / Amber -

Indicators Fault / Green - Power / Red - Supply Voltage (V) 230

Alarm

Voltage TypeACBattery TypeLead AcidPower Consumption (W)1.6TechnologiesRadioLINK

Dimensions & Weights

 Depth (mm)
 100
 Height (mm)
 295

 Width (mm)
 323
 Product weight (kg)
 0.894

Packaged weight (kg) 1.201

Approvals & Warranty

EN 60065:2002 + A12:2011 / EN

Certification/Approvals 50130-4:2011 / EN 61000-6-3:2007 + Warranty 5 year warranty

A1:2011 / EN 300 220-2 (V.2.4.1)

EAN Number 5099383004809

Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

