

Ei407



RadioLINK Manual Call Point



- Allows for remote triggering of an alarm system
- Non-breaking, re-settable front plates
- 10 year Lithium battery powered
- RadioLINK Wireless interconnection
- 5 year guarantee



Description

The Ei407 RadioLINK Manual Call Point is an emergency device that when activated triggers all wirelessly interconnected alarms. It is powered by a tamper proof, 10 year sealed in lithium cell giving a completely wire free installation

Technical

| | | | |
|---------------------------|---|---------------------|------------------|
| RF Frequency (MHz) | 868.499 | RF Range (m) | >100 in free air |
| Indicators | Green - Power / Amber - Low battery / Red - RF transmission | Battery Type | Lithium primary |
| Technologies | RadioLINK | | |

Dimensions & Weights

| | | | |
|-----------------------------|------|----------------------------|------|
| Depth (mm) | 72 | Height (mm) | 100 |
| Width (mm) | 116 | Product weight (kg) | 0.22 |
| Packaged weight (kg) | 0.27 | | |

Approvals & Warranty

| | | | |
|--------------------------------|-----------------------------|-----------------|-----------------|
| Certification/Approvals | EN 300 220-3 / EN 301 489-3 | Warranty | 5 year warranty |
| EAN Number | 5099383004090 | | |

Environmental

| | | | |
|---------------------------|-------|-------------------------------|-----------|
| Humidity Range (%) | 15-95 | Temperature Range (°C) | -10 to 40 |
|---------------------------|-------|-------------------------------|-----------|