## Ei603CRF



### RadioLINK Heat Alarm



- Heat sensor responds to heat build-up from large flaming fires (triggers at 58°C)
- 9V Alkaline Battery included
- RadioLINK Wireless interconnection
- Kitemarked to BS 5446-2:2003
- 5 year guarantee



#### Description

The Ei603CRF RadioLINK Heat Alarm is powered by an Alkaline battery. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

#### Technical

Sensor Type	Heat (A1)	RF Frequency (MHz)	868.499	
RF Range (m)	>100 in free air	Indicators	Red - Fault / Blue - RF transmission	
Battery Type	Alkaline PP3	Technologies	RadioLINK	
Dimensions & Weights				

# Depth (mm)65Height (mm)Width (mm)120Product weight (kg)Packaged weight (kg)0.246

#### Approvals & Warranty

Certification/Approvals	BS 5446-2:2003 / EN 300 220-1 / EN 301 489-1	Warranty	5 year warranty
EAN Number	50993830016148		
Environmental			

 Humidity Range (%)
 15-95
 Temperature Range (°C)
 -10 to 40



120

0.196

www.aico.co.uk | 01691 664100 | enquiries@aico.co.uk