Ei630iRF

Radiol INK+ Heat Alarm



- Heat sensor responds to heat build-up from large flaming fires (triggers at 58°C)
- AudioLINK+ data extraction technology
- 10 year Lithium battery powered
- RadioLINK+ Wireless interconnection
- Kitemarked to BS 5446-2:2003
- 5 year guarantee





Kitchen

Garage



Description

The Ei630iRF RadioLINK+ Heat Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

Technical

Sensor Type Heat (A1) RF Frequency (MHz) 868.499

Red - Power Up, Alarm, Silence

RF Range (m) >100 in free air Indicators Mode, Fault / Blue - RF

transmission

Battery Type Lithium primary Technologies AudioLINK+ / RadioLINK+

Dimensions & Weights

 Depth (mm)
 64
 Height (mm)
 122

 Width (mm)
 122
 Product weight (kg)
 0.206

Packaged weight (kg) 0.248

Approvals & Warranty

Certification/ApprovalsBS 5446-2:2003 / EN 300 220-1 / EN 301 489-1
Warranty
5 year warranty

EAN Number 5099383010275

Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

