

Ei650iRF



RadioLINK+ Optical Smoke Alarm



- Optical sensor with dust compensation technology
- 10 year Lithium battery powered
- Built in AudioLINK+ data extraction technology
- RadioLINK+ wireless interconnection
- Kitemarked to BS EN14604:2005
- 5 year guarantee



Hallway



Landing



Living Room



Dining Room



Bedroom



RadioLINK+®



AudioLINK+®

Description

The Ei650iRF RadioLINK+ Optical Smoke Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

Technical

Sensor Type	Optical - with dust compensation	RF Frequency (MHz)	868.499
RF Range (m)	>100 in free air	Indicators	Red - Fault / Blue - RF transmission / Green - Monitoring
Battery Type	Lithium primary	Technologies	AudioLINK+ / RadioLINK+

Dimensions & Weights

Depth (mm)	55	Height (mm)	125
Width (mm)	120	Product weight (kg)	0.215
Packaged weight (kg)	0.255		

Approvals & Warranty

Certification/Approvals	BS EN 14604:2005 / EN 300 220-1 / EN 301 489-1	Warranty	5 year warranty
EAN Number	5099383005837		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------